

Material Safety Data Sheet

Pure Resin Company Limited

Revision Date: 15th, June, 2009

Product Name: PMB101, PMB101E, PMB101-BK

Ion exchange resin, mixture of Hydroxide Form Anion Exchange Resin and Hydrogen Form Cation Exchange Resin

1. Company Information: Pure Resin Company Limited
Factory Address: Hangzhou Gulf Chemical Zone,
Shangyu, Zhejiang, China 312369
Marketing Dept. Address: Room 1806-1808, Jinfeng Mansion,
No. 281 Zhong He Zhong Road
Hangzhou, Zhejiang, China 310003
Telephone: +86-571-87211518
Fax: +86-571-87211508

2. Composition/Ingredients:

Trimethylamine functionalized
chlormethylated copolymer
of styrene and divinylbenzene
in the hydroxide form

CAS# 69011-18-3, Content:20-30%

Sulfonated copolymer of styrene and
Divinylbenzene in the hydrogen form.

CAS# 69011-20-7, Content:20-30%

Water

CAS# 7732-18-5, Content:40-60%

3. Physical/Chemical Data:

Boiling Point: Not Applicable
Vapor Pressure(MM HG): Not Applicable
Evaporation Rate (water = 1): 1
Appearance & Odor: Yellow, black solid beads.
No to low odor.
Specific Gravity: 1.2 (water = 1)
Melting Point (deg. F): Not applicable
Solubility in Water: Insoluble
Thermal: May yield oxides of carbon and nitrogen
Vapor Density: Not Applicable

Product Hazard Rating	Scale
Toxicity = 0	0 = Negligible
Fire = 0	1 = Slight
Reactivity = 0	2 = Moderate
Special – N/A	3 = High
	4 = Extreme

4. Fire & Explosion Hazard Data

Flammable Limits:

800 ° F

Unusual Fire & Explosion Hazards:

Product is not combustible until moisture is removed, then resin starts to burn in flame at 230° C. Autoignition occurs above 500° C. Possible fire.

Combustion Products:

Alkylbenzenes, vinylbenzenes, naphthalene, benzaldehydes, phenol, carbon dioxide, water, organic amines, chlorine, nitrogen oxides, ammonia, methyl chloride.

Extinguishing Media:

Water, CO₂, Talc, Dry Chemical

Special Fire Fighting Procedures:

MSHA/NIOSH approved self-contained breathing gear.

5. Reactivity Data

Stability:

Stable

Conditions to Avoid:

Temperatures above 400° F

Hazardous by Products:

See Section 3 above for possible combustion products.

Materials to avoid contact with:

Strong oxidizing agents (i.e. nitric acid)

Hazardous Polymerization:

Material does not polymerize

Storage:

Store in a cool dry place

6. Health Hazards & Sara (Right to Know)

Emergency First Aid Procedures:

Contact with eyes can and skins can cause irritation.

Skin Absorption:

Skin absorption is unlikely due to physical properties.

Ingestion:

Single dose oral LD50 has not been determined. Single does oral toxicity is believed to be low. No hazards anticipated from ingestion incidental to industrial exposure.

Inhalation:

Vapors are unlikely due to physical properties.

Systemic & Other Effects:

No specific data available, however, repeated exposures are not anticipated to cause any significant adverse effects.

Carcinogenicity:

Not Applicable

Sara – title 3, sections 311 & 312:

All ingredients are non-hazardous

7. First Aid

Eyes:

Irrigate immediately with water for at least 5 minutes. Mechanical irritation only.

Skin:

No adverse effects anticipated by this route of exposure.

Ingestion:

No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

Inhalation:

No adverse effects anticipated by this route of exposure.

8. Control Measures

Respiratory protection:

Not required for normal uses if irritation occurs from breathing-get fresh air!

Eye protection:

Splash goggles

Ventilation:

Normal

Protective Gloves:

Not required.

9. Safe handling procedures

In Case of Spills:

Sweep up material and transfer to containers. Use caution – the floor will be slippery!

Disposal Method:

Bury resin in licensed landfill or burn in approved incinerator according to local, state, and federal regulations. For resin contaminated with hazardous material, dispose of mixture as hazardous material according to local, state and federal regulations.

10. Additional Information:

Special precautions to be taken in handling and storage:

Practice reasonable care and caution. Metal equipment with feed, regenerant, resin form, and effluent of that process. Every different salt or ionic form of an ion exchange resin is a separate chemical. If you use an ion-exchange resin for ion-exchange purposes and then remove the by-product resin from its vessel or container prior to recovery of the original or another form of the resin or of another chemical, the by-product resin must be listed on the TSCA Inventory(unless an exemption is

TSCA Considerations:

applicable) It is the responsibility of the customer to ensure that such isolated, recycled by-product resins are in compliance with TSCA. Failure to comply could result in substantial civil or criminal penalties being assessed by the Environmental Production Agency.

11. Regulatory Information:

Notice:

(Not meant to be all-inclusive—selected regulations represented.)

The information herein is presented in good faith and believed to be accurate as of the effective date shown above.

However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations.